Four Star Chemical 24-HOUR 3137 26th Street EMERGENCY MATERIAL SAFETY Los Angeles Ca 90023 TELEPHONE DATA SHEET (323) 266-7111 (800) 255-3924 ADVANCED FLOW ENGENEERING, INC AIR FILTER OIL, GOLD, 6.5 OZ PRODUCT ID NO.: 33933 PAGE: 1 EFFECTIVE DATE: 08/22/13 PRODUCT ID NO.: 33933

DATE PREPARED: 08/22/13

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

PRODUCT DESCRIPTION: ADVANCED FLOW ENGENEERING, INC AIR FILTER OIL, GOLD, 6.5 OZ D.O.T. PROPER SHIPPING NAME: LIMITED OUANTITY NFPA CODES: HEALTH - 1 FLAMMABILITY - 3 CORROSIVE - 0 REACTIVITY - 0 CUSTOMER SUPPLIED PEL: N/D TLV: N/D CAS #: NOT AVAILABLE HYDROCARBON PROPELLANT PEL: 800 PPM CAS #: 68476-86-8 TLV: 800 PPM "\*" If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section. BOILING POINT FOR PRODUCT: NOT DETERMINED VAPOR PRESSURE FOR PRODUCT: < 80 psi @ 65 Deg F VAPOR DENSITY FOR PRODUCT: NOT DETERMINED SPECIFIC GRAVITY: 0.80 - 0.9.0 V.O.C. (GRAMS PER LITER): NOT DETERMINED WATER SOLUBILITY: NOT DETERMINED APPEARANCE: AMBER OIL SPRAY FLASH POINT(TCC): LEVEL 3 AEROSOL EXPLOSIVE LIMIT (PRODUCT): LOWER - N/D UPPER - N/D 04.20 GENERAL HAZARD:

Combustible liquid, can form combustible mixtures at temperatures

MATERIAL SAFETY DATA SHEET Four Star Chemical 3137 26th Street Los Angeles Ca 90023 (323) 266-7111 24-HOUR EMERGENCY TELEPHONE (800) 255-3924

## ADVANCED FLOW ENGENEERING, INC AIR FILTER OIL, GOLD, 6.5 OZ

PRODUCT ID NO.: 33933 PAGE: 2

FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boilover. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distnce along the ground or surface to ignition sources where they may ignite or explode.

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue. SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an

existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100
ppm) are irritating to the eyes and the respiratory tract, may cause
headaches, dizziness, anesthesia, drowsiness, unconsciousness, and
other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

## FIRST AID

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention. SKIN CONTACT: Flush with large amounts of water; use soap it available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention

INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

## PRECAUTIONS

SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant

MATERIAL SAFETY DATA SHEET	Four Star Chemical 3137 26th Street Los Angeles Ca 90023 (323) 266-7111	24-HOUR EMERGENCY TELEPHONE (800) 255-3924
PRODUCT ID NO.: 33933	ADVANCED FLOW ENGENEERING, INC AIR FILTER OIL, GOLD, 6.5 OZ	PAGE: 3
<pre>************************************</pre>		
06.20 STABILITY: Stable		
CONDITIONS TO AVOID: Temperatures above 130 degree F.		
HAZARDOUS POLYMERIZATION: Will not occur		
MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents		
HAZARDOUS DECOMPOSITION PRODUCTS: None ====================================		
procedures. Emp which are press mitted waste ma disposal author ======== SECTION V SEC08.20	Consult local authorities for proper w oty de-pressurized containers can not k surized or contain liquid must be dispo- anagement facility. Consult Federal, S rities for approved procedures. /III - PROTECTIVE EQUIPMENT TO BE USED F: Use adequate level exhaust ventilati carbon monoxide may be generated, sp tion may be required.	be reused. Cans osed of in a per- State, and local ========= Lon. Note: Where
	Local exhaust recommended when appro control employee exposure. Based on contamination level and work use a respirator approved by NIOSH/MS	ing limits of
EYES: Face shield and goggles or chemical goggles should be worn.		
GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.		
	TT. Chandrad and all the start	

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed 3137 26th StreetMATERIAL SAFETYLos Angeles Ca 90023DATA SHEET(323) 266-7111

24-HOUR EMERGENCY TELEPHONE (800) 255-3924

ADVANCED FLOW ENGENEERING, INC AIR FILTER OIL, GOLD, 6.5 OZ

PRODUCT ID NO.: 33933

PAGE: 4

===== SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED(CONTINUED) ==== containers. Wash contaminated clothing and dry before reuse.

Four Star Chemical

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

======= SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS ====== SEC09.45

- HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing containers follow standard safety practices for handling chemicals.
- GENERAL COMMENTS: Do not store at temperatures above 120 degree F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.
- PRECAUTIONARY STATEMENTS: Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

This product was evaluated by Four Star Chemical and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.