

INSTALLATION INSTRUCTIONS Part Number E-0782

This filter fits: See catalog for current applications

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures MUST be followed to ensure the proper fit and seal of the K&N® air filter.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

NOTE: To gain access to the air filter, it is recommended that the air box is removed from the vehicle.

- 1. Remove the stock air filter. Note that you will be re-using 4 of the screws to install the K&N[®] filter.
- 2. Install the K&N® filter into the air box with the K&N® logo facing outward. Fig. 1
- 3. Ensure that it is centered and press down firmly to seat it in the air box. Fig. 2
- 4. Place the supplied brackets into the grooves on the filter and install them using 4 of the screws removed in Step 1. Fig. 3
- 5. Ensure that the screws are fully tightened and verify that the brackets are touching the air box. Fig. 4
- 6. Reinstall the air box.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 3



Fig. 2



Fig. 4