



INSTALLATION INSTRUCTIONS

Part Number: HA-7417

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

1. Remove the dirty air filter.
2. Clean all sealing surfaces in the air box.
3. Remove the o-ring from the perimeter of the OE air filter. (Fig. 1 & 2)
NOTE: The K&N air filter utilizes the OE o-ring and hardware.
4. Install the OE o-ring into the groove on the K&N® air filter. (Fig.3)
5. Install the K&N® air filter into the air box using the OE screws.
6. Reinstall the air box lid to complete the installation.
7. With the K&N® air filter installed, clean an area on the air box and apply K&N® Stop Decal. The decal will help notify others that this is a reusable air filter.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig.1



Fig.2



Fig.3

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.